

## Auto PAC 300 SSM-ST Stainless Side Seal

The Auto PAC 300 SSM-ST Stainless unit is designed for harsh or wet environments. The body and most external hardware are made from 304 stainless steel. Other external parts are made from high impact plastic for outstanding moisture protection. In addition, the Auto PAC 300 SSM-ST gives you even greater moisture protection than comparable units by using stainless steel for critical strapping head parts, and the strap accumulator system. Finally, to protect against water splash the Auto PAC 300 SSM-ST has a stainless steel bottom splash pan, and a special heat transformer inside the body helps dispel moisture and reduce condensation. The Auto PAC 300 SSM-ST is also available in a fully automatic version. In addition to all the standard features found on the Auto PAC 300, the stainless side seal version has several key operating features that make it perfect for tough applications:

- **Lubrication Free Strapping Head**  
For consistent, reliable operation.
- **Auto Feeding**  
Loading strap is automatic, activated by pressing the feed switch.
- **Jam Free Automatic Re-Feeding**  
In the event of any feeding problems, the strap is automatically re-fed into the strapping head, and the machine returns to the ready position.
- **Loop Ejection**  
Missed straps are automatically ejected from the machine, and the Auto PAC 300 SSM-ST re-sets itself.
- **End of Strap Sensor**  
If the coil does not have enough strap to complete the cycle, the Auto PAC 300 SSM-ST ejects the short piece, and the machine is immediately ready for a new coil.
- **Optional Adjustable Stainless Table**
- **Remote Foot Controller**
- **Dual Controls**  
Full control panel on the front and an abbreviated operator's panel on the back allows operation from either side.
- **Stainless Splash Panels and a Heat Generating Transformer**  
To minimize moisture.
- **Electronic Tension**  
Tension is controlled electronically, yielding consistent tension.
- **CE Certified**

### TECHNICAL SPECIFICATIONS




Dimensions: 56.3"L x 25.2"D x 68.1"H  
 Strapping Head Height: 26.2"  
 Package Size: Minimum- 5"W x 4"H  
 Maximum- Depends on arch size  
 (See chart for available sizes)  
 Weight: 550 lbs. (Without optional table)  
 Tension Range: 15 – 150 lbs.  
 Speed: 30 cycles per minute  
 Strap Size: 3/8", 9mm – 1/2", 12mm  
 Core Size: 8x8, 9x8  
 Power Requirements: 220V, Three phase 50/60 Hz

**PLEASE NOTE:** Although the Auto Pac 300 SSM-ST has many features to enhance its performance in harsh environments, it is not a wash down machine. Using it as a wash down unit will void the warranty.



Height	25.6"	33.4"	41.3"	49.2"	57.0"	64.9"	72.8"	80.7"	88.6"
Width	650mm	850mm	1050mm	1250mm	1450mm	1600mm	1850mm	2050mm	2250mm
15.7" 400mm									
23.6" 600mm		Standard							
31.5" 800mm									
39.4" 1000mm									
47.2" 1200mm									
55.1" 1400mm									

### AVAILABLE ARCH SIZES (INCHES/MM) AUTO PAC 300 SSM-ST STAINLESS SIDE SEAL STANDARD UNITS

	AVAILABLE IN 1/2" AND 3/8" STRAP
	AVAILABLE FOR 1/2" HEAVY DUTY STRAP (500 LBS. OR GREATER)
	NOT AVAILABLE