

All PAC steel strapping is manufactured in the United States to ASTM specification #D3953-05. PAC steel strapping is consistent in width, gauge and finish. Published break strengths are average and meet, or exceed, industry standards. PAC stocks both regular duty and high tensile at several locations. In addition to the stock sizes listed, we can also supply specialty products on request.

Regular Duty Steel Strapping

Regular duty steel strapping is manufactured from cold rolled steel. All PAC regular duty steel can be used in manual and pneumatic tools, as well as automatic steel strapping heads.

High Tensile Steel Strapping

High tensile steel strapping is manufactured from cold rolled steel and heat treated to maximize break strength and ductility. High tensile steel provides additional break strength and shock resistance for your toughest applications.

Stock Steel Strapping

| PRODUCT | COIL WIDTH (inches) | THICKNESS (inches) | AVERAGE BREAK (lbs.) | YIELD (ft./lb.) | AVERAGE COIL WEIGHT (lbs.) | COILS PER PALLET |
|---|------------------------|-----------------------|-------------------------|--------------------|-------------------------------|---------------------|
| Oscillated Wound, Regular Duty Steel | | | | | | |
| 3/8 x .015 | 3/8 | .015 | 665 | 52.29 | 80 | 12 |
| 1/2 x .015 | 1/2 | .015 | 890 | 39.22 | 100 | 12 |
| 1/2 x .020 | 1/2 | .020 | 1180 | 29.42 | 100 | 12 |
| 1/2 x .023 | 1/2 | .023 | 1350 | 25.58 | 100 | 12 |
| 5/8 x .020 | 5/8 | .020 | 1470 | 23.53 | 100 | 12 |
| 5/8 x .023 | 5/8 | .023 | 1690 | 20.46 | 100 | 12 |
| 3/4 x .020 | 3/4 | .020 | 1765 | 19.61 | 100 | 12 |
| 3/4 x .023 | 3/4 | .023 | 2025 | 17.05 | 100 | 12 |
| Oscillated Wound, High Tensile Steel | | | | | | |
| 1/2 x .020HT | 1/2 | .020 | 1485 | 29.42 | 100 | 12 |
| 5/8 x .020HT | 5/8 | .020 | 1855 | 23.53 | 100 | 12 |
| 5/8 x .023HT | 5/8 | .023 | 2130 | 20.46 | 100 | 12 |
| 3/4 x .025HT | 3/4 | .025 | 2770 | 15.69 | 100 | 12 |
| 3/4 x .029HT | 3/4 | .029 | 3205 | 13.30 | 100 | 12 |
| Ribbon Wound, High Tensile Steel | | | | | | |
| 11/4 x .029HT | 11/4 | .029 | 5530 | 8.11 | 100 | 20 |

Standard finish on PAC steel strapping is black, painted and waxed. Alternative finishes are available on request. Steel strapping is sold by the hundred weight in full pallet quantities only.



Portable Coils

Steel portable coils are used in a variety of applications where a full coil of steel is not needed or is not practical. All portable coils are ribbon wound in a self-dispensing carton.

| PRODUCT | COIL LENGTH (feet) | STRAP WIDTH (inches) | STRAP THICKNESS (inches) | AVERAGE BREAK (lbs.) | WEIGHT (lbs.) |
|------------------------------------|-------------------------------|---------------------------------|-------------------------------------|---------------------------------|--------------------------|
| Regular Duty Portable Coils | | | | | |
| 3/8 x .015-300 | 300 | 3/8 | .015 | 665 | 6 |
| 1/2 x .015-300 | 300 | 1/2 | .015 | 890 | 8 |
| 1/2 x .020-300 | 300 | 1/2 | .020 | 1180 | 10 |
| 1/2 x .023-300 | 300 | 1/2 | .023 | 1350 | 11 |
| 5/8 x .015-300 | 300 | 5/8 | .015 | 1125 | 10 |
| 5/8 x .020-300 | 300 | 5/8 | .020 | 1470 | 13 |
| 5/8 x .023-300 | 300 | 5/8 | .023 | 1690 | 14 |
| 3/4 x .015-300 | 300 | 3/4 | .015 | 1350 | 12 |
| 3/4 x .020-300 | 300 | 3/4 | .020 | 1765 | 15 |
| 3/4 x .023-300 | 300 | 3/4 | .023 | 2025 | 18 |
| High Tensile Portable Coils | | | | | |
| 1/2 x .020HT-300 | 300 | 1/2 | .020 | 1485 | 10 |
| 5/8 x .020HT-300 | 300 | 5/8 | .020 | 1855 | 13 |
| 5/8 x .023HT-300 | 300 | 5/8 | .023 | 2130 | 14 |
| 3/4 x .025HT-280 | 280 | 3/4 | .025 | 2770 | 19 |
| 3/4 x .029HT-200 | 200 | 3/4 | .029 | 3205 | 22 |

