

PAC

STAINLESS STEEL STRAPPING MACHINERY

PSM 1412-MARINE and PSM1412-SS3...

Two outstanding semi-automatic alternatives for harsh environments

PAC Strapping Products features two excellent stainless steel strappers for harsh environments. These units feature a side mounted strapping head to allow moisture to drain through the table instead of through the strapping head. Adjustable strapping tables are standard and allow the operator to strap a wide range of packages. Both machines utilize the proven strapping head perfected in our best selling PSM1412-IC3A, and both machines utilize a 302 stainless steel body, plus a number of features to address harsh environments. The list of features below will assist you in your selection of the right machine for your environment.

PSM1412-SS3

- 302 stainless steel body
- Stainless steel head parts
- IP Standard 20
- Non wash down unit

PSM1412-MARINE

- 302 stainless steel body
- All parts are either stainless, or corrosion resistant
- IP Standard 54
- GFI circuit protected
- Special design for runoff and overspray
- Protected control box
- Internal heater (Option)
- Wash down unit

TECHNICAL SPECIFICATIONS

Dimensions:	26.5"W x 41"D x 64"H
Table Height:	15 to 27" (adjustable)
Package Size:	Minimum 3.25"W x 1.25"H
Maximum Package Weight:	130 lbs.
Machine Weight:	250 lbs.
Tension:	10 to 100 lbs.
Cycle Speed:	2.5 seconds per cycle
Strap Size:	1/4" to 5/8" (5mm to 15mm)
Core Size:	8x8, 9x8
Power Requirements:	110V, Single phase 50/60 Hz



OPERATOR FRIENDLY CONTROL PANEL

PAC *Strapping Products Inc.*

307 National Road, Exton, PA 19341 • 1-800-523-7752 Toll Free • (610) 363-8805 • (610) 363-7349 Fax

Visit our website at- www.strapsolutions.com



© Copyright 2008. PAC Strapping Products, Inc.

PAC

STAINLESS STEEL STRAPPING MACHINERY

PSM 1412-MARINE and PSM1412-SS3...

Two outstanding semi-automatic alternatives for harsh environments

PAC Strapping Products features two excellent stainless steel strappers for harsh environments. These units feature a side mounted strapping head to allow moisture to drain through the table instead of through the strapping head. Adjustable strapping tables are standard and allow the operator to strap a wide range of packages. Both machines utilize the proven strapping head perfected in our best selling PSM1412-IC3A, and both machines utilize a 302 stainless steel body, plus a number of features to address harsh environments. The list of features below will assist you in your selection of the right machine for your environment.

PSM1412-SS3

- 302 stainless steel body
- Stainless steel head parts
- IP Standard 20
- Non wash down unit

PSM1412-MARINE

- 302 stainless steel body
- All parts are either stainless, or corrosion resistant
- IP Standard 54
- GFI circuit protected
- Special design for runoff and overspray
- Protected control box
- Internal heater (Option)
- Wash down unit

TECHNICAL SPECIFICATIONS

Dimensions:	26.5"W x 41"D x 64"H
Table Height:	15 to 27" (adjustable)
Package Size:	Minimum 3.25"W x 1.25"H
Maximum Package Weight:	130 lbs.
Machine Weight:	250 lbs.
Tension:	10 to 100 lbs.
Cycle Speed:	2.5 seconds per cycle
Strap Size:	1/4" to 5/8" (5mm to 15mm)
Core Size:	8x8, 9x8
Power Requirements:	110V, Single phase 50/60 Hz



OPERATOR FRIENDLY CONTROL PANEL

PAC *Strapping Products Inc.*

307 National Road, Exton, PA 19341 • 1-800-523-7752 Toll Free • (610) 363-8805 • (610) 363-7349 Fax

Visit our website at- www.strapsolutions.com



© Copyright 2008. PAC Strapping Products, Inc.