

**Pneumatic sealer**

---

**Characteristics**

---

Strapping qualities:	Uniflex and Ultraflex max. 1100 N/mm <sup>2</sup> / 160'000 psi
Strapping dimensions:	widths 19.0 – 32.0 mm / 3/4 – 1 1/4"
	thicknesses 0.63 – 1.00 mm / .025 - .040"
Weight:	4.2 kg / 9.3 lbs
Average seal strength:	Approx. 75 %
Seals:	Overlap seals
Type of joint:	Double notch upcut joint
Tensioning:	With separate tensioner model A452
Two different working versions:	Version N = Handle 90° to the strap (normal) Version P = Handle parallel to the strap

**Advantages**

---

- The pneumatic sealer can be used easily with one hand only
- The safe upcut double notch joint is accomplished in one strike
- The seal safety mechanism prevents poor seal joints as a result of faulty operation of the tool by the user
- The tool can be supplied with the handle in a 90° angle to the strap (N-version) or with the handle parallel to the strap (P-version), the user may select the right tool for his application

**Chart of types model A461 – Version N = Handle 90° to the strap**

Item No.	Model	Width		Uniflex		Ultraflex	
				Thicknesses		Thicknesses	
		mm	inch	mm	inch	mm	inch
13.4310	A461/19/0.63-0.70/N	19	¾"	0.63-0.70	.025-.028	0.63-0.70	.025-.028
13.4510	A461/32/0.80-0.90/N	32	1 ¼"	0.80-0.90	.031-.035	0.80-0.90	.030-.035

Uniflex = Regular duty strapping max. 850 N/mm<sup>2</sup> / 123'000 psi  
 Ultraflex = High tensile strapping max. 1100 N/mm<sup>2</sup> / 160'000 psi