

Auto PAC 300

A broad range of features in a reliable strapper, priced less than competing brands...

The Auto PAC 300 is a proven, reliable strapper. It is ideal for moderate to high volume applications where 9mm (3/8") or 12mm (1/2") strap is the preferred material. The Auto PAC 300 is fast, consistent, and reliable. In addition, it has all the "user friendly" features, usually found on machines costing thousands of dollars more. The Auto PAC 300 is completely supported with one of the best warranties in the industry, over 99% parts availability within 24 hours, and unlimited, free telephone support for the life of the machine.

Standard features on the Auto PAC 300 include:

- **Lubricated Free Strapping Head**
The strapping head never needs lubrication.
- **Auto Feeding**
Loading strap is automatic, activated by pressing the feed switch.
- **Jam Free Automatic Re-Feeding**
In the event of any feeding problems, the strap is automatically re-fed into the strapping head, and the machine returns to the ready position.
- **Loop Ejection**
Missed straps are automatically ejected from the machine, and the Auto PAC 300 re-sets itself.
- **End of Strap Sensor**
If the coil does not have enough strap to complete the cycle, the Auto PAC 300 ejects the short piece, and the machine is immediately ready for a new coil
- **Three Activation Methods**
The Auto Pac 300 can be activated manually, with a foot pedal, or with a standard photocell.
- **Electronic Tension**
Tension is controlled electronically, yielding consistent tension.
- **Improved Speed**
Up to 30 cycles per minute.
- **CE Certified**



Width >	25.6"	33.4"	41.3"	49.2"	57.0"	64.9"	72.8"
Height	650mm	850mm	1050mm	1250mm	1450mm	1600mm	1850mm
15.7" 400mm							
23.6" 600mm	Standard	Standard					
31.5" 800mm							
39.4" 1000mm							
47.2" 1200mm							

AVAILABLE ARCH SIZES (INCHES/MM) AUTO PAC 300 STANDARD UNITS

- AVAILABLE IN 1/2" AND 3/8" STRAP
- AVAILABLE IN 1/2" HEAVY DUTY STRAP (500LBS. OR GREATER)
- NOT AVAILABLE
REQUIRES A STRAP OF .028" THICK OR GREATER.

i **TECHNICAL
SPECIFICATIONS**

*All dimensions refer to an arch size of
33.4"(850mm)W x 23.6"(600mm)H

Dimensions:	56.3"L x 24.4"D x 60.6"H
Table Height:	31.9"
Package Size:	Minimum - 5"W x 1¼"H Maximum - Depends on arch size (see chart for available sizes)
Weight:	485lbs.
Tension Range:	15 - 150 lbs.
Speed:	30 cycles per minute
Strap Size:	3/8", 9mm - 1/2", 12mm
Core Size:	8x8, 9x8
Power Requirements:	110V, Single phase 50/60 Hz